

**CCSE****Instructions:**

This is a sample test. It is designed to provide a flavor of the actual certification test. Review of these specific questions does not constitute adequate preparation for the test. However, for practice, make sure you read each of the test items below carefully. Select the SINGLE response from the “a”, “b”, “c”, or “d” options that BEST answers or completes the item. Have fun, and good luck.

- 1) You have accidentally blocked access on indefinite basis for a partner network that requires access to an internal web server. Which of the following would clear that specific entry from the SAM table? (0010)
  - a) `fw sam -D`
  - b) `fw sam -I <mode> <ip address>`
  - c) `fw sam -C <mode> <ip address>`
  - d) `fw sam -I <mode> <ip address>`
  
- 2) When you install a security policy, the `rulebase.fws` file is compiled into a \_\_\_\_\_ file. (0001)
  - a) `*.C`
  - b) `*.def`
  - c) `*.h`
  - d) `*.pf`
  
- 3) To allow a management server to execute remote commands utilizing `fw sam`, an administrator needs to edit the `product.conf` file and set the Management value to 1. (0100)
  - a) True
  - b) False
  
- 4) To back up a Security Policy, an administrator needs to make copies of which of the following files? (0010)
  - (1) `objects.C`
  - (2) `rulebases.fws`
  - (3) all `*.pf` files
  - (4) `fwauth.NDB`
  - a) 1, 3
  - b) 2, 4
  - c) 1, 2, 4
  - d) 1, 2, 3, 4
  
- 5) You have installed the enterprise version of FireWall-1 in a client-server configuration, with the management server on one machine and the firewall module on another machine. On the management server in the `control.map` file, you require `fwa1` for all communication with the firewall module. However, in the `control.map` file on the firewall module, you have required all communication with the management server to use `S/Key`. Which of the following statements correctly define what will happen when the management server attempts to install a security policy on the firewall? (0010)
  - a) `S/Key` will be used to authenticate the attempt.
  - b) The policy will not be installed due to the conflicting `control.map` files.
  - c) `fwa1` will be used to encrypt the attempt.
  
- 6) When implementing high availability, it is recommended to synchronize firewalls on different platforms. (0100)
  - a) True
  - b) False

- 7) The user-defined program \_\_\_\_\_ can be used to monitor the logging activity of a rule and issue specific alerts when a condition is met. (0100)
- a) alertd
  - b) alertf
  - c) alertj
  - d) alertg
- 8) \_\_\_\_\_ is the FireWall-1 load-balancing algorithm that determines the load of each physical server. (1000)
- a) Server Load
  - b) Round Trip
  - c) Round Robin
  - d) Domain
- 9) \_\_\_\_\_ is the FireWall-1 load-balancing algorithm that determines trips between the firewall and each physical server. (1000)
- a) Server Load
  - b) Round Trip
  - c) Round Robin
  - d) Domain
- 10) \_\_\_\_\_ is the FireWall-1 load-balancing algorithm that chooses the physical server closest to the client. (0100)
- a) Server Load
  - b) Round Trip
  - c) Round Robin
  - d) Domain

Sample Exam Key

1) C

2) D

3) B

4) C

5) C

6) B

7) B

8) A

9) A

10) B